

LAKE DECATUR PRIVATE BUOY REGULATIONS

LAKE MANAGEMENT DIVISION

424-2837

General Regulations

1. Buoy owners are responsible for purchase, installation, maintenance and removal.
2. Buoy tops are to be marked with the owner's dock number. If the owner does not have a dock then the owner's address is to be used.
3. Buoys are to be secured only with metal chain, wire cable and metal hardware.
4. Anchors are to weigh at least 50 pounds.
5. Buoys are to be removed by November 15 of each year to avoid ice damage and/or drift.
6. Buoys not properly maintained are to be immediately removed by the owner.
7. Buoys are to be one of two types: no wake or mooring.

No Wake Buoys

8. No wake buoys are to be inland waterway buoys, 9 inch diameter minimum, (Rotocast #RB962, Roylan #B1147R, or approved equal).
9. Message on no wake buoys are to be "SLOW NO WAKE" with circle symbol.
10. No wake buoys are to be located 200 feet from shore line.

Mooring Buoys

11. Mooring buoys are to be inland waterway buoys 16 inch diameter minimum, (Rotocast #FB-16P, Rotocast #TMB-1624, Roylan #B1145 or approved equal).
12. Colors are to be white with blue stripe.
13. Mooring buoys are to be located within 50 feet of shore line.

Suppliers

| | |
|-----------------------|--------------|
| Rotocast | 800-351-1363 |
| Smith & Nephew Roylan | 800-228-3693 |